



芯位																																																										
接线颜色	<table border="1"> <tr><td>1</td><td>BK 黑</td><td></td></tr> <tr><td>2</td><td>BN 棕</td><td></td></tr> <tr><td>3</td><td>BU 蓝</td><td></td></tr> </table>	1	BK 黑		2	BN 棕		3	BU 蓝		<table border="1"> <tr><td>1</td><td>BK 黑</td><td></td></tr> <tr><td>2</td><td>BU 蓝</td><td></td></tr> <tr><td>3</td><td>BN 棕</td><td></td></tr> <tr><td>4</td><td>WH 白</td><td></td></tr> </table>	1	BK 黑		2	BU 蓝		3	BN 棕		4	WH 白		<table border="1"> <tr><td>1</td><td>BK 黑</td><td></td></tr> <tr><td>2</td><td>BU 蓝</td><td></td></tr> <tr><td>3</td><td>GNYE 黄绿</td><td></td></tr> <tr><td>4</td><td>BN 棕</td><td></td></tr> <tr><td>5</td><td>WH 白</td><td></td></tr> </table>	1	BK 黑		2	BU 蓝		3	GNYE 黄绿		4	BN 棕		5	WH 白		<table border="1"> <tr><td>1</td><td>BK 黑</td><td></td></tr> <tr><td>2</td><td>BU 蓝</td><td></td></tr> <tr><td>3</td><td>YE 黄</td><td></td></tr> <tr><td>4</td><td>BN 棕</td><td></td></tr> <tr><td>5</td><td>WH 白</td><td></td></tr> <tr><td>6</td><td>GN 绿</td><td></td></tr> </table>	1	BK 黑		2	BU 蓝		3	YE 黄		4	BN 棕		5	WH 白		6	GN 绿	
1	BK 黑																																																									
2	BN 棕																																																									
3	BU 蓝																																																									
1	BK 黑																																																									
2	BU 蓝																																																									
3	BN 棕																																																									
4	WH 白																																																									
1	BK 黑																																																									
2	BU 蓝																																																									
3	GNYE 黄绿																																																									
4	BN 棕																																																									
5	WH 白																																																									
1	BK 黑																																																									
2	BU 蓝																																																									
3	YE 黄																																																									
4	BN 棕																																																									
5	WH 白																																																									
6	GN 绿																																																									
接线规格	3x16AWG	4x16AWG	5x18AWG	6x18AWG																																																						
外壳材质	铜/镀镍	铜/镀镍	铜/镀镍	铜/镀镍																																																						
锁紧螺母	铜/镀镍	铜/镀镍	铜/镀镍	铜/镀镍																																																						
安装板材质	PA66	PA66	PA66	PA66																																																						
触点材质	黄铜镀金	黄铜镀金	黄铜镀金	黄铜镀金																																																						
绝缘电阻	$\geq 100M\Omega$	$\geq 100M\Omega$	$\geq 100M\Omega$	$\geq 100M\Omega$																																																						
使用温度	-25℃~+85℃	-25℃~+85℃	-25℃~+85℃	-25℃~+85℃																																																						
防护等级	IP65	IP65	IP65	IP65																																																						
接头螺纹	7/8-16UNF	7/8-16UNF	7/8-16UNF	7/8-16UNF																																																						
插拔周期	$\geq 100$	$\geq 100$	$\geq 100$	$\geq 100$																																																						
密封圈	丁晴	丁晴	丁晴	丁晴																																																						
额定电流	13A	9A	9A	9A																																																						
额定电压	300V	300V	300V	300V																																																						

开孔尺寸			配件螺母			安装方式
						 板前安装
PG13.5	M20x1.5	G1/2-14NPT	PG13.5	M20x1.5	G1/2-14NPT	

型号	开孔尺寸	型号	开孔尺寸	针-7/8-引线式 PG13.5-M20x1.5- G1/2-板前插座
3针 TFE7/8A3M.09H050	PG13.5	5针 TFE7/8A5M.09H050	PG13.5	
4针 TFE7/8A4M.09H050	PG13.5	6针 TFE7/8A6M.09H050	PG13.5	
3针 TFE7/8A3M.08H050	M20x1.5	5针 TFE7/8A5M.08H050	M20x1.5	
4针 TFE7/8A4M.08H050	M20x1.5	6针 TFE7/8A6M.08H050	M20x1.5	
3针 TFE7/8A3M.05H050	G1/2-14NPT	5针 TFE7/8A5M.05H050	G1/2-14NPT	
4针 TFE7/8A4M.05H050	G1/2-14NPT	6针 TFE7/8A6M.05H050	G1/2-14NPT	签字 _____ 日期 _____
				上海奕坚电气科技有限公司